

## F09

ECOFRIENDLY DECORATIVE COATINGS

### APPLICATIONS

- Ecofriendly decorative fine layer Spray Cork coating for long-lasting protection and renovation of walls and facades.
- Finish coating for external insulation systems, VIPEQ THERM ETICS.
- Fine decorative coating for internal walls.

### FORMULATION

Mixture of selected cork particles with different types of water based resins, mineral filler, stabilizer and special additives.

### SPECIFICATIONS

Appearance	Doughy product
Final texture	Fine
Colour	Natural brown, off-white, extrawhite and range of colours
Density	0.5-0.7 g/cm <sup>3</sup>
Granulometry	0.4-0.5 mm

### CHARACTERISTICS

- Vapour-permeable
- Rainwater proof on vertical walls.
- Flexible, prevents from retraction fissures.
- Continuous thermal coating, improving insulation on thermal bridges.
- Improves acoustic comfort reducing resonance.

### SUBSTRATES

Traditional mortar, concrete, bricks, corrugated steel sheet, wood, PVC, expanded polystyrene (EPS), extruded polystyrene (XPS), single layer mortar, on exterior and interior walls, plaster and plasterboard on interior walls.

Old paint or synthetic coating providing they are in good condition and attached to the substrate.

CORK FIX adhesive paste and lime mortars used in VIPEQ THERM ETICS systems.

The substrate must be clean, dust-exempt, dry and free of oils and grease. Curing of cement mortar renderings must be fully finished. Level flatness of the substrate with a suitable repairing mortar or CORK FIX.

For highly absorbent substrates, it is advisable to previously apply a primer.

### INSTRUCTIONS FOR USE

There are two components inside the container. Stir cork emulsion with the component II inside a hod, by an electric mixer until the dough is homogeneous. In case of coloured coating, pour the colourant and stir the mixture again. Some water can be added to achieve a proper viscosity using the colourant bottle.

The product must be applied by mechanical projection in two or more layers. Estimated drying time between layers is 24h, although it varies depending on ambient humidity and temperature.

- Application standard thickness: 1.5 - 2 mm.
- Dry touch: 30 minutes (ambient temperature 20°C)
- Total drying: 12-24 hours
- Estimated Performance for a 1.5 - 2 mm. thick coating:
  - Standard colours: 1.3-1.5 kg/m<sup>2</sup>
  - Extra-white colour: 1.8 kg/m<sup>2</sup>
- Application temperature: from +5°C to + 45°C

### RECOMMENDATIONS

Thoroughly mix the product by an electric mixer (1,800W and 780 rpm) using an extra-fast VIPEQ 152 type mixing rod until the dough is homogeneous. The extra-white colour may require a slightly longer stirring.

Use adhesive tape for limiting working areas, covering window frames or making decorative drawings on facades.

Tools must be cleaned with soap and water before the product is dry. Otherwise they should be kept underwater with detergent for at least one day. Then, thoroughly brush the remaining product.

### STORAGE

The product must be kept away from sunlight exposure, temperatures above 45°C or below -2°C. In its original container tightly closed and protected from moisture: 1 year.

### PACKAGING

12 kg. plastic pail. 432 kg pallet (36 pails).

### RISK SYMBOLS

- S2 Keep out of the reach of children
- S7 Keep container tightly closed

### DISCLAIMER

The information and recommendations given in this technical data sheet reflect our current knowledge, laboratory tests and experience. For this reason, our guarantee is limited to the quality of the product supplied. This company shall not assume any liability arising from misuse of our products.